

CERO / CERO PLUS

Cero and Cero Plus is our superior entrance matting designed for buildings with high traffic usage. In service for many years, they have proven to stand up to extreme foot traffic. Cero / Cero Plus provides 24/7 protection and superior cleaning properties.

Features:

- Effectively absorbs and traps moisture, dirt and grease
- Nylon / Microfiber yarn provides a durable and robust solution for commercial applications
- Yarn's long-lasting, fade resistance maintains the mats' visual appeal while the thick pile gives a plush, cushioned feel underfoot
- Cero Plus features additional bands of heavy-duty nylon monofilament fibers - provide exceptional scraping ability, facilitating easy removal of coarse dirt/debris, with enhanced durability
- Specially formulated PVC compound backing provides a secure slip resistant base, preventing moisture leak through to floors



Cero (Charcoal, Ash and Brown)

Applications:

- Designed for prolonged daily use, which optimal uses in high traffic areas such as lobbies, public entrances and hallways in hotels public building, malls, hospitals, entertainment venues, etc.

PRODUCT SPECS—Cero*

- **Cero Yarn Type:** Nylon/Microfiber Blend
- **Cero Plus Yarn Type:** Nylon/Microfiber Blend with Nylon Monofilaments
- **Pile construction:** Tuft Cut Pile
- **Pile Height:** Approx. 6.5 mm; 8mm (total height with backing)
- **Pile Weight:** Approx. 700g/m² (weight before dye)
- **Dyeing Process:** Solution dyed
- **Backing:** PVC Compound (NFSI Certified)
- **Total Weight:** Approx. 2.6 kg/m²
- **Max. water temperature:** 60°C / 140°F
- **Fire resistance classification:** BS4790, CPSC FF 1-70, CAN/CGSB-4.2 No. 27.6-M91



Cero Plus (Charcoal and Brown)

*Due to ongoing product improvements, we reserve the right to alter mat specifications as required

11 - 130 Konrad Crescent
Markham, ON L3R 0G5 Canada



www.rismatfloorguard.ca
sales@floorguard.net
1-855-881-8666

RECOMMENDED MAINTENANCE/CARE INSTRUCTIONS:

- Regular thorough cleaning using an upright vacuum cleaner is a must
- Periodic cleaning by injection/extraction methods using a light or medium grade carpet extractor with soft brush power head
- Water temperature should not exceed 60°C / 140°F
- Do not use floor scrubbers, floor burnishers, steamers, pressure/power washers

AVAILABLE SIZES:

- Custom sizes available (using standard 2m wide rolls)



LIMITED WARRANTY:

Cero and Cero Plus Mats come with manufacturer's 2 year limited warranty against defective materials and workmanship

